

Ordering information

Z-5™

REF	Balloon Diameter (mm)	Balloon Length (cm)	Introducer Size (FR)	Shaft Size (FR)	Usable Length (cm)	Guide Wire (Inches)	Maximum Volume (CC)
SPT002	9.5	0.95	5	4	50	0.014	1
SPT003	13.5	1.35	6	5	50	0.021	2

PTS®

REF	Balloon Diameter (mm)	Balloon Length (cm)	Introducer Size (FR)	Shaft Size (FR)	Usable Length (cm)	Guide Wire (Inches)	Rated Burst (ATM)
PTS203	20.0	3.0	8	8	80	0.035	1.5
PTS204	20.0	3.0	8	8	110	0.035	1.5
PTS253	25.0	3.0	8	8	80	0.035	1.5
PTS254	25.0	3.0	8	8	110	0.035	1.5
PTS303	30.0	3.0	8	8	80	0.035	1.0
PTS304	30.0	4.0	8	8	80	0.035	1.0
PTS305	30.0	5.0	8	8	80	0.035	1.0
PTS306	30.0	3.0	8	8	110	0.035	1.0
PTS307	30.0	4.0	8	8	110	0.035	1.0
PTS308	30.0	5.0	8	8	110	0.035	1.0
PTS403	40.0	3.0	9	8	80	0.035	0.5
PTS404	40.0	4.0	9	8	80	0.035	0.5
PTS405	40.0	5.0	9	8	80	0.035	0.5
PTS406	40.0	3.0	9	8	110	0.035	0.5
PTS407	40.0	4.0	9	8	110	0.035	0.5
PTS408	40.0	5.0	9	8	110	0.035	0.5

PTS-X™

REF	Balloon Diameter (mm)	Balloon Length (cm)	Introducer Size (FR)	Shaft Size (FR)	Usable Length (cm)	Guide Wire (Inches)	Rated Burst (ATM)
PTSX101	10.0	1.0	6	6	80	0.035	2.5
PTSX102	10.0	2.0	6	6	80	0.035	2.5
PTSX103	10.0	3.0	6	6	80	0.035	2.5
PTSX104	10.0	1.0	6	6	110	0.035	2.5
PTSX105	10.0	2.0	6	6	110	0.035	2.5
PTSX106	10.0	3.0	6	6	110	0.035	2.5
PTSX122	12.0	2.0	6	6	80	0.035	2.0
PTSX123	12.0	3.0	6	6	80	0.035	2.0
PTSX124	12.0	2.0	6	6	110	0.035	2.0
PTSX125	12.0	3.0	6	6	110	0.035	2.0
PTSX152	15.0	2.0	6	6	80	0.035	2.0
PTSX153	15.0	3.0	6	6	80	0.035	2.0
PTSX154	15.0	4.0	6	6	80	0.035	2.0
PTSX155	15.0	2.0	6	6	110	0.035	2.0
PTSX156	15.0	3.0	6	6	110	0.035	2.0
PTSX157	15.0	4.0	6	6	110	0.035	2.0
PTSX203	20.0	3.0	8	8	80	0.035	1.5

Ordering information

PTS-X™							
REF	Balloon Diameter (mm)	Balloon Length (cm)	Introducer Size (FR)	Shaft Size (FR)	Usable Length (cm)	Guide Wire (Inches)	Rated Burst (ATM)
PTSX204	20.0	4.0	8	8	80	0.035	1.5
PTSX205	20.0	3.0	8	8	110	0.035	1.5
PTSX206	20.0	4.0	8	8	110	0.035	1.5
PTSX253	25.0	3.0	8	8	80	0.035	1.5
PTSX254	25.0	4.0	8	8	80	0.035	1.5
PTSX255	25.0	3.0	8	8	110	0.035	1.5
PTSX256	25.0	4.0	8	8	110	0.035	1.5
PTSX303	30.0	3.0	8	8	80	0.035	1.0
PTSX304	30.0	4.0	8	8	80	0.035	1.0
PTSX305	30.0	5.0	8	8	80	0.035	1.0
PTSX306	30.0	3.0	8	8	110	0.035	1.0
PTSX307	30.0	4.0	8	8	110	0.035	1.0
PTSX308	30.0	5.0	8	8	110	0.035	1.0
PTSX353	35.0	3.0	9	8	80	0.035	1.0
PTSX354	35.0	4.0	9	8	80	0.035	1.0
PTSX355	35.0	5.0	9	8	80	0.035	1.0
PTSX356	35.0	6.0	9	8	80	0.035	1.0
PTSX357	35.0	3.0	9	8	110	0.035	1.0
PTSX358	35.0	4.0	9	8	110	0.035	1.0
PTSX359	35.0	5.0	9	8	110	0.035	1.0
PTSX360	35.0	6.0	9	8	110	0.035	1.0
PTSX403	40.0	3.0	9	8	80	0.035	0.5
PTSX404	40.0	4.0	9	8	80	0.035	0.5
PTSX405	40.0	5.0	9	8	80	0.035	0.5
PTSX406	40.0	6.0	9	8	80	0.035	0.5
PTSX407	40.0	3.0	9	8	110	0.035	0.5
PTSX408	40.0	4.0	9	8	110	0.035	0.5
PTSX409	40.0	5.0	9	8	110	0.035	0.5
PTSX410	40.0	6.0	9	8	110	0.035	0.5

MULTI-TRACK™

REF	Introducer Size (FR)	Shaft Size (FR)	Usable Length (cm)	Guide Wire (Inches)	Flow Rate (ml/sec)	Maximum Injection (PSI)
MMTA2560	4.0	2.5	60	0.021	3.5	1000
MMTA2580	4.0	2.5	80	0.021	2.7	1000
MMTA03100	5.0	3.0	100	0.025	4.0	1000
MMTA0380	5.0	3.0	80	0.025	5.5	1000
MMTA0360	5.0	3.0	60	0.025	6.5	1000
MMTA04100	6.0	4.0	100	0.035	11.0	1000
MMTA0480	6.0	4.0	80	0.035	13.0	1000
MMTA05100	7.0	5.0	100	0.035	20.0	1000
MMTA0580	7.0	5.0	80	0.035	22.0	1000
MMTA06100	8.0	6.0	100	0.035	25.0	1000